	<b>SAFETY DATA SHEET</b>	Page : 1 / 12
	<b>Premium Gear Lube</b>	Revision nr : 1.2
		Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0109S</b>

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture  
Trade name/designation : Premium Gear Lube  
Product code : 92-858007Q01, 92-858058QB1, 92-858059QB1, 92-858061QB1, 92-858062QB1, 92-8M0121963, 92-8M0133945  
Document no. : 766-01-0109S

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Industrial use, Professional use, Consumer use  
Use of the substance/mixture : Lubricants

#### 1.2.2. Uses advised against

No data available

### 1.3. Details of the supplier of the safety data sheet

Brunswick Marine EMEA  
Parc industriel de Petit-Rechain, Avenue Mercury 8  
4800 Verviers - Belgium  
T +32 (0)87 32 32 11  
[bme.compliance@brunswick.com](mailto:bme.compliance@brunswick.com)

### 1.4. Emergency telephone number

Emergency number : 0032 3 575 55 55  
This telephone number is available 24 hours per day, 7 days per week.

Country	Official advisory body	Address	Emergency number
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	+353 1 809 21 66 (public, 8am - 10pm, 7/7) +353 01 809 2566 (Professionals, 24/7)
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre, Wolfson Unit	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0844 892 0111 (UK only, 24/7, healthcare professionals only)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]


Aquatic Chronic 3 H412

Full text of H statements : see section 16

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word : -  
Hazard statements (CLP) : H412 - Harmful to aquatic life with long lasting effects.  
Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P273 - Avoid release to the environment.

	<b>SAFETY DATA SHEET</b>	Page : 2 / 12
		Revision nr : 1.2
	<b>Premium Gear Lube</b>	Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0109S</b>

Extra phrases : P501 - Dispose of contents/container to an approved waste disposal plant  
: EUH208 - Contains Polysulfides, di-tert-Bu, Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl. May produce an allergic reaction.

### 2.3. Other hazards

Other hazards : Results of PBT and vPvB assessment : Not applicable.

## **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Polysulfides, di-tert-Bu	(CAS-No.) 68937-96-2 (EC-No.) 273-103-3	0,5 - 0,6	Skin Sens. 1, H317 Aquatic Chronic 4, H413
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	(CAS-No.) RR-108536-5 (EC-No.) 931-384-6	0,3 - 0,4	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411
2,6-di-tert-butylphenol	(CAS-No.) 128-39-2 (EC-No.) 204-884-0	0,2 - 0,3	Skin Irrit. 2, H315 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
naphthalene	(CAS-No.) 91-20-3 (EC-No.) 202-049-5 (EC Index) 601-052-00-2	< 0,01	Carc. 2, H351 Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-statements: see section 16

## **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

Additional advice : First aider: Pay attention to self-protection. Concerning personal protective equipment to use, see section 8. Never give anything by mouth to an unconscious person. In case of doubt or persistent symptoms, consult always a physician. Show this safety data sheet to the doctor in attendance. Treat symptomatically.

Inhalation : Remove person to fresh air and keep comfortable for breathing. In case of doubt or persistent symptoms, consult always a physician.

Skin contact : Take off contaminated clothing. Gently wash with plenty of soap and water. In case of doubt or persistent symptoms, consult always a physician.

Eyes contact : Rinse immediately carefully and thoroughly with eye-bath or water. In case of doubt or persistent symptoms, consult always a physician.

Ingestion : Rinse mouth thoroughly with water. Get medical advice/attention.


### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation : The following symptoms may occur: Irritation.

Skin contact : The following symptoms may occur: Irritation.

Eyes contact : The following symptoms may occur: Irritation.

Ingestion : The following symptoms may occur: May cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

	<b>SAFETY DATA SHEET</b>	Page : 3 / 12
	<b>Premium Gear Lube</b>	Revision nr : 1.2
		Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0109S</b>

#### **4.3. Indication of any immediate medical attention and special treatment needed**

No data available

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

Suitable extinguishing media : Water spray. Alcohol resistant foam. dry extinguishing powder. Carbon dioxide.  
 Unsuitable extinguishing media : Strong water jet.

#### **5.2. Special hazards arising from the substance or mixture**

Specific hazards : Non flammable. Heating causes rise in pressure with risk of bursting.  
 Hazardous decomposition products in case of fire : Carbon oxides (CO, CO<sub>2</sub>).

#### **5.3. Advice for firefighters**

Firefighting instructions : Evacuate area. Use water spray or fog for cooling exposed containers. Contain the extinguishing fluids by bunding. Prevent fire fighting water from entering the environment.  
 Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus.  
 Other information : Do not allow run-off from fire-fighting to enter drains or water courses. Dispose of waste in accordance with environmental legislation.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **6.1.1. For non-emergency personnel**

For non-emergency personnel : Evacuate personnel to a safe area. Stay upwind/keep distance from source. Provide adequate ventilation. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Do not breathe vapour/aerosol. Avoid contact with skin, eyes and clothing.

##### **6.1.2. For emergency responders**

For emergency responders : Ensure procedures and training for emergency decontamination and disposal are in place. Concerning personal protective equipment to use, see section 8.

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Notify authorities if product enters sewers or public waters.

#### **6.3. Methods and material for containment and cleaning up**

Methods for cleaning up : Stop leak if safe to do so. Dam up. Clean-up methods - small spillage: Take up liquid spill into absorbent material, e.g.: sand, earth, vermiculite or powdered limestone, Collect in closed and suitable containers for disposal. Clean-up methods - large spillage: Recover large spills by pumping (use an explosion proof or hand pump), Keep in suitable, closed containers for disposal. Dispose of waste product or used containers according to local regulations.


#### **6.4. Reference to other sections**

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

Precautions for safe handling : Provide adequate ventilation. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Do not breathe vapour/aerosol. Avoid contact with skin, eyes and clothing. Take any precaution to avoid mixing with combustibles... See also section 10. Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time). Do not allow to enter into surface water or drains.

	<b>SAFETY DATA SHEET</b>	Page : 4 / 12
		Revision nr : 1.2
	<b>Premium Gear Lube</b>	Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0109S</b>

Hygiene measures : Keep good industrial hygiene. Wash hands immediately after handling the product. When using do not eat, drink or smoke. Keep away from food, drink and animal feedingstuffs. Separate working clothes from town clothes. Take off contaminated clothing. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Store in a dry, cool and well-ventilated place. Refer to the detailed list of incompatible materials in section 10 Stability/Reactivity. Bund storage facilities to prevent soil and water pollution in the event of spillage.

Packaging materials : Keep only in the original container.

### 7.3. Specific end use(s)

Lubricant.

## SECTION 8: Exposure controls/personal protection


### 8.1. Control parameters

naphthalene (91-20-3)		
EU	IOELV TWA (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	10 ppm
Austria	MAK (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Austria	MAK (ppm)	10 ppm
Belgium	Limit value (mg/m <sup>3</sup> )	53 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	10 ppm
Belgium	Short time value (mg/m <sup>3</sup> )	80 mg/m <sup>3</sup>
Belgium	Short time value	15 ppm
Bulgaria	OEL TWA (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Bulgaria	OEL STEL (mg/m <sup>3</sup> )	75 mg/m <sup>3</sup>
Croatia	GVI (granična vrijednost izloženosti) (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Croatia	GVI (granična vrijednost izloženosti) (ppm)	10 ppm
Cyprus	OEL TWA (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Cyprus	OEL TWA (ppm)	10 ppm
Czech Republic	Expoziční limity (PEL) (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	10 ppm
Estonia	OEL TWA (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Estonia	OEL TWA (ppm)	10 ppm
Finland	HTP-arvo (8h) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Finland	HTP-arvo (8h) (ppm)	1 ppm
Finland	HTP-arvo (15 min)	10 mg/m <sup>3</sup>
Finland	HTP-arvo (15 min) (ppm)	2 ppm
France	VME (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
France	VME (ppm)	10 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed-inhalable fraction)
Germany	TRGS 900 Occupational exposure limit value (ppm)	0,4 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed-inhalable fraction)
Gibraltar	8h mg/m <sup>3</sup>	50 mg/m <sup>3</sup>
Gibraltar	8h ppm	10 ppm
Greece	OEL TWA (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>

## Premium Gear Lube

**766-01-0109S**
**naphthalene (91-20-3)**

Greece	OEL TWA (ppm)	10 ppm
Hungary	AK-érték	50 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	10 ppm
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	150 mg/m <sup>3</sup> (calculated)
Ireland	OEL (15 min ref) (ppm)	30 ppm (calculated)
Latvia	OEL TWA (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Latvia	OEL TWA (ppm)	10 ppm
Lithuania	IPRV (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Lithuania	IPRV (ppm)	10 ppm
Luxembourg	OEL TWA (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Luxembourg	OEL TWA (ppm)	10 ppm
Malta	OEL TWA (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Malta	OEL TWA (ppm)	10 ppm
Netherlands	Grenswaarde TGG 8H (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Netherlands	Grenswaarde TGG 15MIN (mg/m <sup>3</sup> )	80 mg/m <sup>3</sup>
Poland	NDS (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Poland	NDSch (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Portugal	OEL TWA (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup> (indicative limit value)
Portugal	OEL TWA (ppm)	10 ppm (indicative limit value)
Portugal	OEL STEL (ppm)	15 ppm
Romania	OEL TWA (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Romania	OEL TWA (ppm)	10 ppm
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Slovakia	NPHV (priemerná) (ppm)	10 ppm
Slovakia	NPHV (Hraničná) (mg/m <sup>3</sup> )	80 mg/m <sup>3</sup>
Slovenia	OEL TWA (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Slovenia	OEL TWA (ppm)	10 ppm
Spain	VLA-ED (mg/m <sup>3</sup> )	53 mg/m <sup>3</sup>
Spain	VLA-ED (ppm)	10 ppm
Spain	VLA-EC (mg/m <sup>3</sup> )	80 mg/m <sup>3</sup>
Spain	VLA-EC (ppm)	15 ppm
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (ppm)	10 ppm
Sweden	kortidsvärde (KTV) (mg/m <sup>3</sup> )	80 mg/m <sup>3</sup>
Sweden	kortidsvärde (KTV) (ppm)	15 ppm
Norway	Grenseverdier (AN) (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Norway	Grenseverdier (AN) (ppm)	10 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m <sup>3</sup> )	75 mg/m <sup>3</sup> (value calculated)
Norway	Grenseverdier (Korttidsverdi) (ppm)	15 ppm (value calculated)
Switzerland	MAK (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Switzerland	MAK (ppm)	10 ppm
Australia	TWA (mg/m <sup>3</sup> )	52 mg/m <sup>3</sup>

	<b>SAFETY DATA SHEET</b>	Page : 6 / 12
		Revision nr : 1.2
	<b>Premium Gear Lube</b>	Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0109S</b>

naphthalene (91-20-3)		
Australia	TWA (ppm)	10 ppm
Australia	STEL (mg/m <sup>3</sup> )	79 mg/m <sup>3</sup>
Australia	STEL (ppm)	15 ppm
Canada (Quebec)	VECD (mg/m <sup>3</sup> )	79 mg/m <sup>3</sup>
Canada (Quebec)	VECD (ppm)	15 ppm
Canada (Quebec)	VEMP (mg/m <sup>3</sup> )	52 mg/m <sup>3</sup>
Canada (Quebec)	VEMP (ppm)	10 ppm
USA - ACGIH	ACGIH TWA (ppm)	10 ppm
USA - IDLH	US IDLH (ppm)	250 ppm
USA - NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
USA - NIOSH	NIOSH REL (TWA) (ppm)	10 ppm
USA - NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	75 mg/m <sup>3</sup>
USA - NIOSH	NIOSH REL (STEL) (ppm)	15 ppm
USA - OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
USA - OSHA	OSHA PEL (TWA) (ppm)	10 ppm

Additional information : Personal air monitoring ;. Room air monitoring. Recommended monitoring procedures


**8.2. Exposure controls**

- Engineering measure(s) : Provide adequate ventilation. Organisational measures to prevent /limit releases, dispersion and exposure. Safe handling: see section 7 .
- Personal protective equipment : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
- Hand protection : Wear chemically resistant gloves (tested to EN374) . The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
- Eye protection : Use suitable eye protection. (EN166): Safety glasses
- Body protection : Wear suitable protective clothing.
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Half-face mask (EN 140). Full face mask (EN 136). Filter type: ABEK + P (EN 141). The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. (EN 137)
- Thermal hazard protection : Not required for normal conditions of use. Use dedicated equipment.
- Environmental exposure controls : Avoid release to the environment. Comply with applicable Community environmental protection legislation.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

- Physical state : Liquid
- Appearance : liquid.
- Colour : Dark amber.
- Odour : Hydrocarbon-like.
- Odour threshold : No data available
- pH : No data available
- Relative evaporation rate (butylacetate=1) : No data available

	<b>SAFETY DATA SHEET</b>	Page : 7 / 12
		Revision nr : 1.2
	<b>Premium Gear Lube</b>	Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0109S</b>

Melting / freezing point	: No data available
Freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: 229,44 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable,liquid,Not applicable
Vapour pressure	: < 1 mmHg
Vapour density	: > 1 (Air = 1.0)
Relative density	: No data available
Density	: 0,8819 g/cm <sup>3</sup>
Solubility	: No data available. Water: Negligible
Partition coefficient n-octanol/water	: No data available
Kinematic viscosity	: 135 mm <sup>2</sup> /s (40 °C) 15,3 mm <sup>2</sup> /s (100 °C)
Dynamic viscosity	: No data available
Explosive properties	: Not applicable. The study does not need to be conducted because there are no chemical groups associated with explosive properties present in the molecule.
Oxidising properties	: Not applicable. The classification procedure needs not to be applied because there are no chemical groups present in the molecule which are associated with oxidising properties.
Explosive limits	: No data available
<b>9.2. Other information</b>	
VOC content	: 0 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

None under normal processing. Reference to other sections: 10.4 & 10.5.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

None under normal processing.

### 10.4. Conditions to avoid

Safe handling: see section 7.

### 10.5. Incompatible materials

Strong oxidizing agents. Safe handling: see section 7.

### 10.6. Hazardous decomposition products

Reference to other sections: 5.2.


## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified (Based on available data, the classification criteria are not met.)

<b>Polysulfides, di-tert-Bu (68937-96-2)</b>	
LD50/oral/rat	6500 mg/kg
<b>2,6-di-tert-butylphenol (128-39-2)</b>	
LD50/oral/rat	> 5000 mg/kg
LD50/dermal/rabbit	> 10 g/kg



	<b>SAFETY DATA SHEET</b>	Page : 8 / 12
		Revision nr : 1.2
	<b>Premium Gear Lube</b>	Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0109S</b>

<b>naphthalene (91-20-3)</b>	
LD50/oral/rat	1110 mg/kg
LD50/dermal/rat	> 2500 mg/kg
LD50/dermal/rabbit	1120 mg/kg
LC50/inhalation/4h/rat	> 340 mg/m <sup>3</sup> (Exposure time: 1 h)

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met.) pH: No data available
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met.) pH: No data available
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met.)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met.)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met.)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met.)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met.)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met.)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met.)

<b>Premium Gear Lube</b>	
Kinematic viscosity	135 mm <sup>2</sup> /s (40 °C)

Other information : Symptoms related to the physical, chemical and toxicological characteristics. For further information see section 4.

## SECTION 12: Ecological information

### 12.1. Toxicity

Environmental properties : Harmful to aquatic life with long lasting effects.

<b>Polysulfides, di-tert-Bu (68937-96-2)</b>	
LC50 fish 1	250 - 500 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	> 1000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [semi-static])

<b>2,6-di-tert-butylphenol (128-39-2)</b>	
EC50 Daphnia 1	0,45 mg/l (Exposure time: 48 h - Species: Daphnia magna)

<b>naphthalene (91-20-3)</b>	
LC50 fish 1	5,74 - 6,44 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	2,16 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	0,4 mg/l (72 h - Skeletonema costatum)
LC50 fish 2	0,11 mg/l Oncorhynchus mykiss
EC50 Daphnia 2	1,96 mg/l (Exposure time: 48 h - Species: Daphnia magna [Flow through])

### 12.2. Persistence and degradability

<b>Premium Gear Lube</b>	
Persistence and degradability	No data available.


<b>naphthalene (91-20-3)</b>	
Persistence and degradability	Readily biodegradable.

### 12.3. Bioaccumulative potential

<b>Premium Gear Lube</b>	
Partition coefficient n-octanol/water	No data available

<b>naphthalene (91-20-3)</b>	
BCF fish 1	30 - 430



	<b>SAFETY DATA SHEET</b>	Page : 9 / 12
		Revision nr : 1.2
	<b>Premium Gear Lube</b>	Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0109S</b>

<b>naphthalene (91-20-3)</b>	
Partition coefficient n-octanol/water	3,6
Bioaccumulative potential	Moderately bioaccumulative.

**12.4. Mobility in soil**

<b>Premium Gear Lube</b>	
Ecology - soil	No data available.

**12.5. Results of PBT and vPvB assessment**

No data available

**12.6. Other adverse effects**

Additional information : No data available

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

Product/Packaging disposal recommendations : Do not allow to enter into surface water or drains. Dispose of empty containers and wastes safely. Safe handling: see section 7. Refer to manufacturer/supplier for information on recovery/recycling. Recycling is preferred to disposal or incineration. If recycling is not possible, eliminate in accordance with local valid waste disposal regulations.

Additional information : Handle contaminated packages in the same way as the substance itself. Dispose of contaminated materials in accordance with current regulations.

European waste catalogue (2001/573/EC, 75/442/EEC, 91/689/EEC) : This material and its container must be disposed of as hazardous waste Waste codes should be assigned by the user based on the application for which the product was used.

**SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

**14.6. Special precautions for user**


Special precautions for user : No data available

**- Overland transport**

No data available

**- Transport by sea**

No data available

	<b>SAFETY DATA SHEET</b>	Page : 10 / 12
		Revision nr : 1.2
	<b>Premium Gear Lube</b>	Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0109S</b>

**- Air transport**

No data available

**- Inland waterway transport**

No data available

**- Rail transport**

No data available

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Code: IBC : No data available.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**15.1.1. EU-Regulations**

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	Premium Gear Lube - Polysulfides, di-tert-Bu - Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl - 2,6-di-tert-butylphenol
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Polysulfides, di-tert-Bu - Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl - 2,6-di-tert-butylphenol
3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	Premium Gear Lube - Polysulfides, di-tert-Bu - Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl - 2,6-di-tert-butylphenol

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 0 %

**15.1.2. National regulations**

**France**

Installations classées :  
Not applicable.

**Germany**


Reference to AwSV : Water hazard class (WGK) 1, Slightly hazardous to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

**Netherlands**

Waterbezuwaarlijkheid : 3 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Saneringsinspanningen : A - In principe niet lozen; zo ja, dan toepassen van beste bestaande technieken

	<b>SAFETY DATA SHEET</b>	Page : 11 / 12
		Revision nr : 1.2
	<b>Premium Gear Lube</b>	Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0109S</b>

SZW-lijst van kankerverwekkende stoffen : None of the components are listed  
 SZW-lijst van mutagene stoffen : None of the components are listed  
 NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed  
 NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed  
 NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out

## SECTION 16: Other information


Indication of changes:

1.1	Product code	Modified	
-----	--------------	----------	--

Abbreviations and acronyms:

	ABM = Algemene beoordelingsmethodiek
	ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin
	ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
	CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC
	IATA = International Air Transport Association
	IMDG = International Maritime Dangerous Goods Code
	LEL = Lower Explosive Limit/Lower Explosion Limit
	UEL = Upper Explosion Limit/Upper Explosive Limit
	REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
	BTT = Breakthrough time (maximum wearing time)
	DMEL = Derived Minimal Effect level
	DNEL = Derived No Effect Level
	EC50 = Median Effective Concentration
	EL50 = Median effective level
	ErC50 = EC50 in terms of reduction of growth rate
	ErL50 = EL50 in terms of reduction of growth rate
	EWC = European waste catalogue
	LC50 = Median lethal concentration
	LD50 = Median lethal dose
	LL50 = Median lethal level
	NA = Not applicable
	NOEC = No observed effect concentration
	NOEL: no-observed-effect level
	NOELR = No observed effect loading rate
	NOAEC = No observed adverse effect concentration
	NOAEL = No observed adverse effect level
	N.O.S. = Not Otherwise Specified
	OEL = Occupational Exposure Limits - Short Term Exposure Limits (STELs)
	PNEC = Predicted No Effect Concentration
	Quantitative structure-activity relationship (QSAR)
	STOT = Specific Target Organ Toxicity
	TWA = time weighted average
	VOC = Volatile organic compounds
	WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act)

Sources of key data used to compile the datasheet : LOLI <http://www.echemportal.org> MSDS.

	<b>SAFETY DATA SHEET</b>	Page : 12 / 12
	<b>Premium Gear Lube</b>	Revision nr : 1.2
		Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0109S</b>

Training advice : Training staff on good practice.  
Other information : Assessment/classification CLP. Article 9. Calculation method.

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Aquatic Acute 1
Aquatic Chronic 1	Hazardous to the aquatic environment - chronic hazard category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - chronic hazard category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - chronic hazard category 3
Aquatic Chronic 4	Hazardous to the aquatic environment - chronic hazard category 4
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, hazard category 1
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH208	Contains Polysulfides, di-tert-Bu, Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl. May produce an allergic reaction.

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830  
Classification according to Regulation (EC) No. 1272/2008 [CLP]  
Labelling according to Regulation (EC) No. 1272/2008 [CLP]

**DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.